
 <p>City of Santa Monica®</p>	<p>City of Santa Monica</p> <p>Plumbing Fixture Flow Rates</p> <p>Non-Residential Buildings</p> <p>2019 Green Building Standards Code</p>	 <p>Eff. 1-01-20</p>
---	---	---

FIXTURE FLOW RATES (SECT 5.303)	
FIXTURE TYPE	MAX ALLOW. FLOW RATE
Showerheads	1.8 gpm @ 80psi
Lavatory faucets, nonresidential	0.5gpm @ 60psi ¹
Kitchen faucets	1.8gpm @ 60psi ²
Wash fountains	1.8gpm/20 [rim space (in.) @60psi]
Metering faucets	0.2 gallons/ cycle
Metering faucets for wash fountains	0.2 (rim space (in.)/20 gpm @60psi)
Water closets	1.28 gallons/flush ³
Urinals, wall mounted	0.125 gallons/flush
Urinals, floor mounted	0.5 gallons/flush

Note: Where complying faucets are unavailable, aerators or other means may be used to achieve reduction

¹ Lavatory Faucets shall not have a flow rate less than 0.8 gpm @ 20psi.

² Kitchen faucets may temporarily increase flow above the max rate, but not above 2.2gpm @60psi and must default to a max flow rate of 1.8gpm @60psi.

³ The effective flush volume of dual flush toilets is defined as the composite, average flush volume of two reduced flushes and one full flush.